

## Eveneer® Prefinished

### Material Handling Guide

Eveneer Prefinished is a real timber veneer sheet, on a timber or laminate support, finished with an acrylic polish, supplied as a 1mm thick sheet or on the substrate of your choice. Suitable for interior joinery and furniture it is recommended for vertical and light-duty horizontal use.

- Not recommended for outdoor use.
- Protect from direct, bright or reflected sunlight.
- Do not expose to bright light, excessive heat, high-humidity, chemicals, water and other liquids.
- Store flat at least 200mm from the floor and keep in strapped pack covered with plastic sheeting and/or a cover sheet and protected from light and humidity until ready to use. Keep the humidity range of the storage area between 40% and 70% (RH).
- Sheets and panels should be allowed to acclimatize for 24 – 48 hours before commencing production.
- Taking into consideration the dimensional tolerances of the substrate, a <3.5mm/1m bow on G1S liner backed laminated panels and <2.5mm/1m on G2S laminated panels is within industry standards.
- Leave the clear protective film on the surface while working the veneer. Do not peel back the film from part of the sheet for an extended period of time as this may cause the exposed area to change colour in relation to the unexposed area.
- Do not drag/slide sheets and/or panels across one another.
- To apply Eveneer Prefinished sheets manually, contact your glue supplier to determine the most suitable product for your application. Follow the glue manufacturer's instructions carefully. The use of contact glue is not recommended.
- Seal all exposed/cut edges on your finished product to prevent moisture absorption into the timber layer. This is most easily done with an aqua stop pen.
- When cleaning the face after edging please trial first on an offcut as some cleaners/thinners can cloud the lacquered face of both edging and sheet.
- For ongoing cleaning, warm soapy water with a damp, non-abrasive cloth is recommended. Do not use abrasive cleaners or pads to clean the face material. Do not use harsh chemicals. If you do want to try a chemical, please do so on an off-cut.
- As in all wood working operations, it is essential that adequate protection is taken against the contact and the breathing of wood dust when processing, and that normal workplace hygiene practices are followed.

For further information, *Recommendations for Use* and *Terms and Conditions* please refer to [eltongroup.com/eveneer-prefinished](http://eltongroup.com/eveneer-prefinished)

