

Eveneer Profiles

Material Handling Guide

Eveneer Profiles are 3D profiled raw timber sheets. Suitable for interior joinery and furniture they are recommended for vertical use. Eveneer Profiles require finishing and may be polished with a range of finishes suitable for interior timber products.

- Not recommended for outdoor use.
- Protect from direct, bright or reflected sunlight.
- Do not expose to bright light, excessive heat, high-humidity, chemicals, water and other liquids.
- Avoid even temporary contact with water and other liquids and avoid any moisture on the product surface.
- Store flat at least 200mm from the floor and keep in strapped pack covered with plastic sheeting and/or a cover sheet and protected from light and humidity until ready to use. Keep the humidity range of the storage area between 40% and 70% (RH).
- Sheets and panels should be allowed to acclimatize for 24 – 48 hours before commencing production.
- Do not drag/slide sheets and/or panels across one another.
- To protect from the effects of light and dry air or wind, always keep the raw timber completely covered with a panel of flat plywood, MDF, etc.
- When transporting raw timber, care must be taken to keep it dry, protected from air/wind and clean from road dirt and dust.
- Coat immediately after sanding, because raw wood exposed to air may oxidise and discolour.
- Seal all exposed/cut edges on your finished product to prevent moisture absorption into the timber layer.
- As in all wood working operations, it is essential that adequate protection is taken against the contact and the breathing of wood dust when processing, and that normal workplace hygiene practices are followed.

For further information and *Terms and Conditions* please refer to eltongroup.com/eveneer-profiles

