

Eveneer. Prefinished

Material Handling Guide

- Eveneer Prefinished is a real timber veneer sheet, on a laminate support, polished with an acrylic polyurethane.
- Eveneer Prefinished is supplied with a clear protective film to the face. We recommend that you leave the film on the surface while working the veneer.
- Do not peel back the film from part of the sheet for an extended period of time as this may cause the exposed area to change colour in relation to the unexposed area.
- Taking into consideration the dimensional tolerances of the substrate, a <3.5mm/1m bow on G1S liner backed laminated panels and <2.5mm/1m on G2S laminated panels is standard.
- Store sheets and/or panels flat and protected from light and humidity.
- Do not drag/slide sheets across one another.
- When cleaning the face after edging please trial first on an offcut as some cleaners/thinners can cloud the lacquered face of both edging and sheet.
- Seal all exposed/cut edges on your finished product to prevent moisture absorption into the timber layer. This is most easily done with an aqua stop pen.
- For ongoing cleaning, warm soapy water with a damp, non-abrasive cloth is recommended. Do not use abrasive cleaners or pads to clean the face material. Do not use harsh chemicals. If you do want to try a chemical, please do so on an off-cut.
- Eveneer Prefinished is recommended for vertical and light-duty horizontal use.
- Eveneer Prefinished is not recommended for outdoor use.
- For further information and Terms and Conditions please call us on 1300 133 481 or refer to our website www.eltongroup.com/eveneer-prefinished

